

I. CONSTRUCTION

Center conductor: Solid Bare Copper Clad Aluminum	Diameter	.108 inches
Dielectric: Gas Injected Foam Polyethylene		.455
Shield: Aluminum-Polyester-Aluminum-Adhesive Tape		.461
: 33 GA Tinned Copper Braid (90%k)		.490
Jacket: Black Low Smoke Low Toxicity Non-halogen FR Polyethylene		.590 +/- .015"

Print: " LMR®-600-75-LSZH COAXIAL CABLE T TIMES MICROWAVE SYSTEMS
PH +1(203)949-8400 dmy ft"

II. ENVIRONMENTAL and MECHANICAL PROPERTIES

Weight: 131 pounds per 1000 feet
 Operating temperature: -40°C to +85°C
 Minimum bend radius: 1-1/2 inch
 Flame & smoke: **SEE NOTES BELOW**

III. ELECTRICAL PROPERTIES

Impedance: 75 ohms
 Capacitance: 15.6 pF per foot
 Velocity: 87 %

Attenuation @	30 MHz:	0.40 dB per 100 feet
Typical (max)	50 MHz:	0.50 dB per 100 feet
	150 MHz:	0.90 dB per 100 feet
	220 MHz:	1.10 dBper 100 feet
	450 MHz:	1.60 dB per 100 feet
	900 MHz:	2.30 dB per 100 feet
	1500 MHz:	3.10 dBper 100 feet
	2000 MHz:	3.70 dB per 100 feet
	2500 MHz:	4.20 dB per 100 feet


Shielding: >90dB

IV. NOTES

1. Flame: Meets IEC-332-1-2, IEC 332-3 CAT.C, UL-VW1, UL-1581, IEE-383, BS-4066-1, BS-4066-3
2. Smoke: Meets IEC-61034-2, NES-711
3. Halogen: Meets IEC-60754-1, BS 6425-1, IEC-60754-2, BS 6425-2
4. MISC: Compliant to EN-45545 (R15/R16), DIN 5510-2, NF F16-101, BS-6853 Standards
5. UV Resistant: Meets UL-1581, 720 Hour UV Exposure
6. Meets NFPA-130 Requirements
7. ROHS Compliant: 2002/95/EC ROHS Directive and Amendment 2011/65/EC

This document contains Times Microwave Systems proprietary information. It shall not be duplicated, used or disclosed in whole or in part to third parties without written authorization from Times Microwave Systems. This data is EAR controlled IAW 15 CFR Part 730-774

Approvals		
Drawn	EP	10/23/2016
CHK		
This Technical Specification is for Reference only		

 TIMES MICROWAVE SYSTEMS Wallingford, CT 06492 (203) 949-8400; (203) 949-8423.Fax			
		LMR-600-75-LSZH	
Size A	CAGE CODE 68999	Drawing No.: AA-11829	

Scale: NA	Rev. (--A)	Sheet: 1 of 1
-----------	------------	---------------